

(12) INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(19) World Intellectual Property  
Organization  
International Bureau



IN 2005 537926

(43) International Publication Date  
12 August 2004 (12.08.2004)

PCT

(11) International Publication Number  
**WO 2004/068642 A1**

(54) International Patent Classification: **H01R 4/02**

889 Yingjun Road, Waigaoqiao Free Trade Zone, Pudong,  
Shanghai 200131 (CN).

(21) International Application Number:  
**PCT/US2004/002820**

(74) Agent: **BEITLER, Robert, J.**; Molex Incorporated, 2222  
Wellington Court, Lisle, IL 60532 (US).

(22) International Filing Date: 29 January 2004 (29.01.2004)

(81) Designated States (unless otherwise indicated, for every  
kind of national protection available): AE, AG, AL, AM,  
AT, AU, ~~AZ~~, BA, BB, BG, BR, BW, BY, BZ, CA, CH, CN,  
CO, CR, ~~CU~~, CZ, DE, DK, DM, DZ, EC, EE, EG, ES, FI,  
GB, ~~GD~~, ~~GE~~, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE,  
KG, KP, ~~KR~~, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD,  
MG, ~~MK~~, ~~MN~~, MW, MX, MZ, NA, NI, NO, NZ, OM, PG,  
PH, ~~PL~~, ~~PT~~, ~~RU~~, SC, SD, SE, SG, SK, SL, SY, TH, TM,  
TN, ~~TR~~, ~~TT~~, ~~UA~~, ~~UG~~, ~~US~~, ~~UZ~~, ~~VE~~, ~~VN~~, ~~YU~~, ~~ZA~~, ~~ZD~~, ~~ZM~~, ~~ZW~~.

(25) Filing Language: English

(26) Publication Language: English

(30) Priority Data:  
0920022 1 29 January 2004 (US)


(72) Inventor: **HAO, Yin** [CN/CN];  
INCORPORATED [US/US]; 2222 Wellington Court,  
Lisle, IL 60532 (US).

(75) Inventor/Applicant (for US only): **HAO, Yin** [CN/CN];

(84) Designated States (unless otherwise indicated, for every  
kind of regional protection available): ARIPO (BY, GH,  
GM, KE, LS, MW, MZ, NA, SD, SL, SZ, TZ, UG, ZM, ZW),  
EUROPEAN (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR,

[Continued on next page]

(54) Title: **CONDUCTIVE TERMINAL AND THE ELECTRICAL CONNECTOR USING THE CONDUCTIVE TERMINAL**



(57) Abstract: A conductive terminal and the electrical connector using the conductive terminal, the conductive terminal is received in a terminal channel defined in an insulative housing of the electrical connector which can transmit signal between an electronic component and a circuit board. The conductive terminal has a first wall, a second wall connecting with the first wall in a certain angle and third wall connecting with the second wall in a certain angle and opposite to the first wall. The conductive terminal forms a mounting portion connecting with the solder ball. The mounting terminal forms a mounting portion connecting with the solder ball. The mounting portion comprises a first horizontal portion extending and bending from one end of the first wall toward the third wall, and a second horizontal portion on the third wall and corresponding to the first horizontal portion toward the first wall. A gap is defined between an end of the second horizontal portion and an end of the first horizontal portion near the second horizontal portion so that the first horizontal portion and the second horizontal portion form a structure for locating the solder ball.

BEST AVAILABLE COPY



GB, GR, HU, IE, IT, LU, MC, NL, PT, RO, SE, SI, SK,  
TR), OAPI (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW,  
ML, MR, NE, SN, TD, TG).

**Published:**

— with international search report

— before the expiration of the time limit for amending the  
claims and to be republished in the event of receipt of  
amendments

*For two-letter codes and other abbreviations, refer to the "Guid-  
ance Notes on Codes and Abbreviations" appearing at the begin-  
ning of each regular issue of the PCT Gazette.*

CONDUCTIVE TERMINAL AND THE ELECTRICAL  
CONNECTOR USING THE CONDUCTIVE TERMINAL

**Field of the Invention:**

The present invention generally relates to a conductive terminal and, more particularly, to a conductive terminal used in an electrical connector which can transmit signals between an electronic component and a circuit board via a solder ball connected with the circuit board.

**Background of the Invention:**

Referring to FIG. 1 to 3, as disclosed in T.W. patent application No. 087216147, the present invention relates to a conductive terminal and an electrical connector ("ZIF") electrically connecting a microprocessor (CPU) and a circuit board used in computer device. The electrical connector 1 comprises an insulative housing 10 and a plurality of conductive terminals 2. Each of the conductive terminals 2 electrically connects with the circuit board 30 through surface mounting technology ("SMT") by pre-setting a solder ball 23 onto an end thereof.

The insulative housing 10 of the electrical connector 1 has a mounting surface 12 on the bottom surface thereof which is positioned proximate to the circuit board 30 and a receiving surface 11 on the top surface thereof for supporting the electronic component. The insulative housing 10 also defines a plurality of through holes 13 extending between the mounting surface 12 and the receiving surface 11.

Each of the conductive terminals 2 respectively received in the corresponding through holes 13 forms a contact portion 20 extending toward the receiving surface 11 and an end portion 21 opposite extending to the mounting surface 12. The end portion 21 has a bottom surface 22 for soldering with the corresponding solder ball 23.

To improve successful rate of pre-setting the solder ball 23 onto the end portion 21 of the conductive terminals 2, the end portion 21 forms a disk-shape plane approximately 90 degrees bending to the contact portion 20 so that the end portion 21 and the mounting surface 12 of the insulative housing 10 are approximately located in the same plane. The plane disk-shape end portion 21 provides a larger area of pre-setting the solder ball 23 so as to steadily pre-set the solder ball 23. In addition, a plurality of protrusions 25 is integrity extending from

the side of the end portion 21 for preventing the solder ball 23 dropping from the bottom surface 22 of the end portion 21.

To applying the SMT of pre-setting the solder ball 23, one end of the conductive terminal 2 must have a structure of easily locating and connecting the solder ball 23. The above method is only one of the resolving schemes with which the end portion of the conductive terminal 2 has different structures to locate and connect the solder ball 23. The present invention provides an improved conductive terminal to locate and connect the solder ball 23.

#### Summary of the Invention:

An object of the present invention is to provide a conductive terminal that easily locates a solder ball and an electrical connector using the conductive terminals.

Another object of the present invention is to provide a conductive terminal enhancing steadiness of soldering with a solder ball.

The conductive terminals of the present invention are received in a plurality of terminal channels of an insulative housing of the electrical connector which can transmit signals between an electronic component and a circuit board.

The conductive terminal has a first wall, a second wall connecting with the first wall in a certain angle and a third wall connecting with the second wall in a certain angle and opposite to the first wall. The conductive terminal forms a contact portion electrically connecting with the electronic component and a mounting portion electrically connecting with the circuit board via the solder ball. The mounting portion comprises a first horizontal portion extending and bending from one end of the first wall toward the third wall, and a second horizontal portion on the third wall and corresponding to the first horizontal portion toward the first wall. A gap is defined between an end of the second horizontal portion and an end of the first horizontal portion near the second horizontal portion so that the first horizontal portion and the second horizontal portion form a structure for locating the solder ball.

The first horizontal portion defines a first recess at its end thereof and the second horizontal portion defines a second recess at its end thereof. The first recess and the second recess form a concavity structure which connects the surface of the solder ball.

When the solder ball contacts with the mounting portion, the solder ball can be received and located in the concavity structure defined by the first recess and the second recess. The melting solder ball flow into the gap between the first horizontal portion

and the second horizontal portion so as to enhance steadiness of soldering between the solder ball and the mounting portion.

Other objects, features and advantages of the invention will be apparent from the following detailed description taken in connection with the accompanying drawings.

5

#### **Brief Description of the Drawings:**

The features of this invention which are believed to be novel are set forth with particularity in the appended claims. The invention, together with its objects and the advantages thereof, may be better understood by reference to the following description taken in conjunction with the accompanying drawings, in which FIGS. 1 through 9 illustrate the elements in the figures and in which:

- FIG. 1 is a partial sectional view illustrating a conventional electrical connector;
- FIG. 2 is a side partial sectional view illustrating of FIG. 1;
- FIG. 3 is a perspective view of a conductive terminal of the conventional electrical connector of FIG. 1;
- FIG. 4 is a perspective view of a conductive terminal inserting into a terminal channel of an insulative housing of the first embodiment of the present invention from under the insulative housing;
- FIG. 5 is a perspective assembled view of FIG. 4 illustrating a solder ball located in a mounting portion of the conductive terminal of the present invention;
- FIG. 6 is a perspective view of the conductive terminal inserting into the terminal channel of the insulative housing of the first embodiment from the above of the insulative housing;
- FIG. 7 is a side view of the solder ball melting and connecting with the conductive terminal of the first embodiment;
- FIG. 8 is a perspective view of the conductive terminal of the second embodiment of the present invention; and
- FIG. 9 is a perspective assembled view of FIG. 8 illustrating the solder ball located in the mounting portion of the conductive terminal of the present invention.

30

#### **Detailed Description of the Disclosed Embodiments:**

While the invention may be susceptible to embodiment in different forms, there is shown in the drawings, and herein will be described in detail, a specific embodiment with the understanding that the present disclosure is to be considered an exemplification of the

principles of the invention, and is not intended to limit the invention to that as illustrated and described herein.

Referring now to FIG. 4 and FIG. 5, a conductive terminal 4 of the present invention used in an electrical connector is similar with the prior art and connects between an electronic component (not shown) and a circuit board (not shown). The conductive terminal 4 pre-sets a solder ball 6 onto an end thereof.

The electrical connector comprises an insulative housing 5 and a plurality of conductive terminals 4.

The insulative housing 5 has a mounting surface 51 which is positioned proximate to the circuit board (such as motherboard of a computer) and a receiving surface 52 for supporting the electronic component (such as central processing unit, "CPU"). The insulative housing 5 defines a plurality of terminal channels 53 extending through the mounting surface 51 and the receiving surface 52. To easily illuminate, it is drawn in the FIGS. that the insulative housing 5 has a single terminal channel 53.

Each conductive terminal 4 is respectively received in the corresponding terminal channels 53. The conductive terminal 4 has a first wall 41, a second wall 42 connecting with one side of the first wall 41 in an approximately 90 degrees angle and a third wall 43 connecting with the other side of the second wall 42 in an approximately 90 degrees angle and opposite to the first wall 41 in some distance. The connecting corner of the first wall 41 and the second wall 42 defines a plurality of hollows 44 so as to make the connecting corner of the first wall 41 and the second wall 42 have lower intensity and the first wall 41 easily bend along the hollows 44. Similarly, the connecting corner of the third wall 43 and the second wall 42 defines a plurality of hollows 44 so as to make the third wall 43 easily bend along the hollows 44 to the second wall 42. When the conductive terminal 4 is respectively received in the corresponding terminal channel 53, one end of the conductive terminal 4 adjacent to the mounting surface 51 forms a mounting portion 401 and the opposite end to the mounting portion 401 of the conductive terminal 4 adjacent to the receiving surface 52 forms a contact portion 402.

The mounting portion 401 comprises a first horizontal portion 45 extending and bending in an approximately 90 degrees from one end of the first wall 41 adjacent to the mounting surface 51 toward the third wall 43, and a second horizontal portion 46 extending and bending in an approximately 90 degrees angle from the third wall 43 adjacent to the mounting surface 51 toward the first wall 41 so that a gap 452 is defined by the ends of the first horizontal portion 45 and the second horizontal portion 46. In this embodiment, referring

to FIG. 5, the first horizontal portion 45, the second horizontal portion 46 and the mounting surface 51 of the insulative housing 5 are approximately in a same plane. The first horizontal portion 45 defines a first recess 451 semicircle depressed to the terminal channel 53 and the second horizontal portion 46 defines a second recess 461 semicircle depressed to the terminal channel 53. The first recess 451 and the second recess 461 forms a concavity structure for receiving the solder ball 6.

The contact portion 402 comprises a first spring arm 47 formed on one side of the first wall 41 adjacent to the receiving surface 52 and a second spring arm 48 formed on one side of the second wall 42 adjacent to the receiving surface 52. A free end of the first spring arm 47 and a free end of the second spring arm 48 are adjacent to form a spring receiving structure to provide an insert arm of an electrical component (not shown) inserting. Because the contact portion 402 is not the point of novelty of the present invention and its principle of electrically connecting is similar with a corresponding structure of the conductive terminal of the ZIF electrical connector (not shown), here it is not illuminated in detail.

Referring to FIG. 4 to FIG. 6, in assembly, the conductive terminal 4 can insert the corresponding terminal channels 53 of the insulative housing 5 from the mounting surface 51 of the insulative housing 5 (referring to FIG. 4) and the conductive terminal 4 can also insert the corresponding terminal channels 53 of the insulative housing 5 from the receiving surface 52 of the insulative housing 5 (referring to FIG. 6). When the conductive terminal 4 can insert the corresponding terminal channels 53 of the insulative housing 5 from the mounting surface 51 of the insulative housing 5, the mounting portion 401 of the conductive terminal 4 can hold the inserting conductive terminal 4. Contrary, when the conductive terminal 4 can also insert the corresponding terminal channels 53 of the insulative housing 5 from the receiving surface 52 of the insulative housing 5, one end of the second wall 42 forms a handle 49 corresponding to the first spring arm 47 and the second spring arm 48 to hold the inserting conductive terminal 4.

Referring to FIG. 4 and FIG. 5, the mounting portion 401 of the conductive terminal 4 locates the solder ball 6 by its first horizontal portion 45 and the second horizontal portion 46. The first recess 451 defined at the end of the first horizontal portion 45 and the second recess 461 defined at the end of the second horizontal portion 46 form a concavity structure which connects the surface of the solder ball 6. When the solder ball 6 contacts with the mounting portion 401, the solder ball 6 can be received and located in the concavity structure defined by the first recess 451 and the second recess 461. So the solder ball 6 need not accurately

align the middle of the mounting portion 401 and easily to locate in the first recess 451 and the second recess 461.

Referring to FIG. 7, a gap 452 is defined between an end of the second horizontal portion 46 and an end of the first horizontal portion 45 near the second horizontal portion 46. When the solder ball 6 melts, tin flow into the gap 452 so that the solder ball 6 not only can respectively solder with the surfaces of the first horizontal portion 45 and the second horizontal portion 46 but also some tin of the solder ball 6 fasten in the gap 452 by embedding so as to enhance steadiness of soldering between the solder ball 6 and the mounting portion 401 of the conductive terminal 4.

Referring to FIG. 8 and FIG. 9, the conductive terminal 4 of the second embodiment of the present invention is a little different from the first embodiment of the present invention. The first horizontal portion 45 and the second horizontal portion 46 of the conductive terminal 4 bend toward the terminal channels 53 so that the first horizontal portion 45 and the second horizontal portion 46 extend in a direction towards the contact portion 402. As such, the first horizontal portion 45 and the second horizontal portion 46 have less than 180 degrees angles and are not in the same plane. The first horizontal portion 45 and the second horizontal portion 46 form a concavity space toward the terminal channels 53 so that when the solder ball 6 contacts with the mounting portion 401, the solder ball 6 can easily be received and located in the mounting portion 401 defined by the first recess 451 and the second recess 461.

The conductive terminal 4 has the first wall 41, the second wall 42 and the third wall 43. The conductive terminal 4 enhances steadiness of locating the solder ball 6 via the mounting portion 401 defined by the first horizontal portion 45 extending from the first wall 41 and the second horizontal portion 46 extending from the third wall 43 and the locating space defined by the first recess 451 defined at the end of the first horizontal portion 45 and the second recess 461 defined at the end of the second horizontal portion 46. The gap 452 is defined between an end of the second horizontal portion 46 and an end of the first horizontal portion 45 near the second horizontal portion 46 to make tin of the melting solder ball 6 flow into and enhance steadiness of soldering with the solder ball 6.

Although the present invention has been illustrated and described with respect to exemplary embodiment thereof, it should be understood by those skilled in the art that the various changes, omissions and additions may be made therein and thereto without departing from the spirit and scope of the present invention as set forth in the appended claims.



CLAIMS:

What is claimed is:

1. A conductive terminal capable of being received in a terminal channel defined in an insulative housing and between an electronic component and a circuit board, having a contact portion electrically connecting with the electronic component and a mounting portion electrically connecting with the circuit board via a solder ball, comprising:
  - 5 a first wall, a second wall connecting with the first wall in a certain angle and a third wall connecting with the second wall in a certain angle and opposite to the first wall, and the mounting portion comprising a first horizontal portion extending and bending from one end of the first wall toward the third wall, and a second horizontal portion on the third wall and corresponding to the first horizontal portion toward the first wall, a gap defined between an
    - 10 end of the second horizontal portion and an end of the first horizontal portion near the second horizontal portion so that the first horizontal portion and the second horizontal portion form a structure for locating the solder ball.
2. The conductive terminal of claim 1 in which the first horizontal portion and the second horizontal portion are in a same plane.
3. The conductive terminal of claim 2 in which the first horizontal portion, the second horizontal portion and the mounting surface of the insulative housing are in a same plane.
4. The conductive terminal of claim 1 in which the first horizontal portion and the second horizontal portion have a certain angle and bend toward the contact portion of the conductive terminal.
5. The conductive terminal of claim 1 in which the first horizontal portion defines a first recess at its end thereof and the second horizontal portion defines a second recess at its end thereof, the first recess and the second recess form a locating space receiving the solder ball.

6. ~~The~~ conductive terminal of claim 1 in which the contact portion comprises a first spring arm ~~formed~~ on one side of the first wall and a second spring arm formed on one side of the second wall corresponding to the first spring arm, and the first spring arm and the second spring arm form a spring receiving structure to connect with the electrical component.

7. ~~The~~ conductive terminal of claim 1 in which one end of the second wall forms a handle.

8. An electrical connector for connecting between an electronic component and a circuit board via a plurality of solder balls soldering onto the circuit board, comprising:

an insulative housing forming a mounting surface adjacent to the circuit board and a receiving surface for supporting the electronic component, the insulative housing defining a plurality of terminal channels extending through the mounting surface and the receiving surface; and

a plurality of conductive terminals respectively received in the corresponding terminal channels, each conductive terminal comprising a first wall, a second wall connecting with the first wall and a third wall connecting with the second wall opposite to the first wall, a first horizontal portion extending and bending from one end of the first wall adjacent to the mounting surface toward the third wall, and a second horizontal portion extending from the third wall and corresponding to the first horizontal portion, a gap defined between an end of the second horizontal portion and an end of the first horizontal portion near the second horizontal portion so that the first horizontal portion and the second horizontal portion form a structure for locating the solder ball.

9. ~~The~~ electrical connector of claim 8 in which the first horizontal portion and the second horizontal portion of the conductive terminal are in a same plane.

10. ~~The~~ electrical connector of claim 9 in which the first horizontal portion, the second horizontal portion and the mounting surface of the insulative housing are in a same plane.


11. ~~The~~ electrical connector of claim 8 in which the first horizontal portion, the second horizontal portion have a certain angle and bend toward the contact portion of the conductive terminal.

12. The electrical connector of claim 8 in which the first horizontal portion defines a first recess at its end thereof and the second horizontal portion defines a second recess at its end thereof, the first recess and the second recess form a locating space receiving the solder ball.


13. The electrical connector of claim 8 in which the contact portion comprises a first spring arm formed on one side of the first wall and a second spring arm formed on one side of the second wall corresponding to the first spring arm, and the first spring arm and the second spring arm form a spring receiving structure to connect with the electrical component.

14. The electrical connector of claim 8 in which one end of the second wall of the conductive terminal forms a handle adjacent to the receiving surface.

1/8




**FIG. 1**



**FIG. 2**

**PRIOR ART**


2/8



**FIG. 3**



4/8



**FIG. 5**

5/8





FIG. 6




6/8




**FIG. 7**

7/8



**FIG. 8**

8/8



**FIG. 9**

# INTERNATIONAL SEARCH REPORT

International Application No  
PCT/004/002820

A. CLASSIFICATION OF SUBJECT MATTER  
IPC 7 H01R4/02

According to International Patent Classification (IPC) or to both national classification and IPC

## B. FIELDS SEARCHED

Minimum documentation searched (classification system followed by classification symbols)  
IPC 7 H01R H05K

Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched

Electronic data base consulted during the international search (name of data base and, where practical, search terms used)

EPO-Internal

## C. DOCUMENTS CONSIDERED TO BE RELEVANT

Category *	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
A	US 5 997 317 A (PEI WEN-CHUN ET AL) 7 December 1999 (1999-12-07) the whole document	1,8

☐ Further documents are listed in the continuation of box C.

☒ Patent family members are listed in annex.

### \* Special categories of cited documents :

- \*A\* document defining the general state of the art which is not considered to be of particular relevance
- \*E\* earlier document but published on or after the international filing date
- \*L\* document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified)
- \*O\* document referring to an oral disclosure, use, exhibition or other means
- \*P\* document published prior to the international filing date but later than the priority date claimed

- \*T\* later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention
- \*X\* document of particular relevance; the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone
- \*Y\* document of particular relevance; the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art.
- \*G\* document member of the same patent family

Date of the actual completion of the international search

30 June 2004

Date of mailing of the international search report

06/07/2004

Name and mailing address of the ISA

European Patent Office, P.B. 5818 Patentlaan 2  
NL - 2280 HV Rijswijk  
Tel (+31-70) 340-2040, Tx. 31 651 epo nl,  
Fax: (+31-70) 340-3016

Authorized officer

Corrales, D

# INTERNATIONAL SEARCH REPORT

Information on patent family members

International Application No  
PCT/004/002820

Patent document cited in search report		Publication date		Patent family member(s)	Publication date
US 5997317	A	07-12-1999	TW	392975 Y	01-06-2000

**This Page is Inserted by IFW Indexing and Scanning  
Operations and is not part of the Official Record**

**BEST AVAILABLE IMAGES**

Defective images within this document are accurate representations of the original documents submitted by the applicant.

Defects in the images include but are not limited to the items checked:

☐ **BLACK BORDERS**

☐ **IMAGE CUT OFF AT TOP, BOTTOM OR SIDES**

☐ **FADED TEXT OR DRAWING**

☐ **BLURRED OR ILLEGIBLE TEXT OR DRAWING**

☐ **SKEWED/SLANTED IMAGES**

☐ **COLOR OR BLACK AND WHITE PHOTOGRAPHS**

☐ **GRAY SCALE DOCUMENTS**

☒ **LINES OR MARKS ON ORIGINAL DOCUMENT**

☒ **REFERENCE(S) OR EXHIBIT(S) SUBMITTED ARE POOR QUALITY**

☐ **OTHER:** \_\_\_\_\_

**IMAGES ARE BEST AVAILABLE COPY.**

**As rescanning these documents will not correct the image problems checked, please do not report these problems to the IFW Image Problem Mailbox.**